

Description

A universal, ultra-fine milled anatase titanium dioxide, with an organic surface treatment, possessing a high degree of whiteness, opacity and dispersibility.

Application

It is used in interior solvent-based and water-based paints. PRETIOX AV01SF is also suitable for undemanding plastic manufacturing applications: injection moulding, rolling, casting, the production of plates, polyolefin products, PVC etc. Ready made products have a limited life time and are intended both for interior or exterior use. It can also be used for the pigmentation of rubber mixtures, and can be used for direct injection into paper pulp, barrier paper, and paper coatings.

Basic characteristics

Grade	anatase pigment
Surface treatment	organic
TiO ₂ content	99 %
Water absorption	20 g/100 g
Classification EN ISO 591	A 1
Classification ASTM D 476	I
Specific gravity	3.9 g/cm ³
Bulk density	390 kg/m ³
Tamped density	700 kg/m ³
CAS No.	13463-67-7
EINECS No.	236-675-5
Colour index	77891 Pigment white 6
REACH Registration No.	01-2119489379-17-0013

Safety

Titanium dioxide PRETIOX is not classified as dangerous under the relevant EC Directives and is not dangerous according to transport regulations. PRETIOX AV01SF complies with the purity requirements on materials and articles intended to come into contact with food as well as with the EC Directives for safety of toys.