

Titanium Dioxide

**PRETIOX R200M**Edition  
1.0 / 2015**Description**

An ultra-fine milled rutile titanium dioxide with an organic surface treatment, possessing a high degree of whiteness, opacity, and dispersibility

**Application**

It can be used in various decorative paints and coatings where extra resistance to climatic conditions is not required, i.e. primers, undercoats, fillers and pastes, interior paints and paints for road markings. A low concentration of volatile substances makes it perfect for use in systems which are sensitive to high levels of heat and humidity. In the paper industry, it is used mainly in the production of barrier papers.

**Basic characteristics**

Grade	rutile pigment
Surface treatment	organic
TiO <sub>2</sub> content	99 %
Oil absorption	16 g/100 g
Classification EN ISO 591	R 1
Classification ASTM D 476	II
Specific gravity	4.2 g/cm <sup>3</sup>
Bulk density	500 kg/m <sup>3</sup>
Tamped density	800 kg/m <sup>3</sup>
CAS No.	13463-67-7
EINECS No.	236-675-5
Colour index	77891 Pigment white 6
REACH Registration No.	01-2119489379-17-0013

**Safety**

Titanium dioxide PRETIOX is not classified as dangerous under the relevant EC Directives and is not dangerous according to transport regulations. PRETIOX R200M complies with the purity requirements on materials and articles intended to come into contact with food as well as with the EC Directive 2012/231 for for safety of toys.