

Titanium Dioxide

**PRETIOX R200P**Edition  
1.0 / 2015

**Description** An ultra-fine milled rutile with an organic treatment, possessing a high degree of whiteness, opacity and dispersibility.

**Application** This grade of TiO<sub>2</sub> is suitable for undemanding plastic manufacturing applications: injection moulding, rolling, casting, the production of plates, polyolefins products, PVC etc. Ready made products have a limited life time and are intended for both interior and exterior use.

<b>Basic characteristics</b>	Grade	rutile pigment
	Surface treatment	organic
	TiO <sub>2</sub> content	99 %
	Oil absorption	16 g/100 g
	Classification EN ISO 591	R 1
	Classification ASTM D 476	II
	Specific gravity	4.2 g/cm <sup>3</sup>
	Bulk density	500 kg/m <sup>3</sup>
	Tamped density	800 kg/m <sup>3</sup>
	CAS No.	13463-67-7
	EINECS No.	236-675-5
	Colour index	77891 Pigment white 6
	REACH Registration No.	01-2119489379-17-0013

**Safety** Titanium dioxide PRETIOX is not classified as dangerous under the relevant EC Directives and is not dangerous according to transport regulations. PRETIOX R200P complies with the purity requirements on materials and articles intended to come into contact with food as well as with the EC Directives for safety of toys.